

SPACEGUARD WIRE MESH STORAGE LOCKERS

WOVEN WIRE PARTITIONS | WELDED WIRE PARTITIONS | VERSATILE MESH ENCLOSURES | RACK AND MEZZANINE GUARDING

SPACEGUARD
PRODUCTS™



MODULAR WIRE MESH STORAGE LOCKERS

- Fully framed doors & panels for quick assembly & durable install
- Offers unrestricted circulation, visibility and fire suppression

FLEXIBLE DESIGN, UNLIMITED OPTIONS

- Standard and custom sizes available
- Single, double, and triple tier configurations
- Woven, welded wire mesh, expanded metal or solid sheet infill
- Swing, slide, and bi-parting door options
- Optional shelves and hang rods
- Finish options for humid or corrosive environments

INDUSTRIAL GRADE, INFINITE APPLICATIONS

- Condo and apartment tenant storage
- Military TA-50 & personnel readiness
- Tack and feed lockers
- Portable military gear lockers
- Portable solutions for hospitality, tradeshow & merchandisers



SPACEGUARD WIRE MESH STORAGE LOCKERS

WOVEN WIRE PARTITIONS | WELDED WIRE PARTITIONS | VERSATILE MESH ENCLOSURES | RACK AND MEZZANINE GUARDING

SPACEGUARD
PRODUCTS™



WIRE MESH CEILING



DIVIDER SHELVES



ADJUSTABLE
PADLOCK HASP

SPECIFICATIONS

PANELS: Constructed standard with 10-gauge wire, welded in a 2" square mesh & 1/4" x 3/4" flat stiffener bars securely welded to 1 1/4" x 1 1/4" x 1/8" angle frames with all joints welded. Available in 6-gauge welded wire, several expanded metal sizes, & solid infill options for various security requirements. Panels come in 90" standard heights & equipped with slotted holes for quick mounting.

OPTIONAL PANELS: *Ceiling panels* are constructed of framed 10-gauge wire mesh and mounted using perforated galvanized slotted angle. *Back panels* consist of 20-gauge galvanized sheet steel, furnished with a 3" x 1/8" hot rolled, flat vertical splice strip to connect backs on adjacent units. *Vertical Flat panel member* is 3" x 1/8" flat stock & punched with six 3/8" x 7/8" slotted holes for bolting to panels & doors at 90° angles.

DIVIDER SHELVES: Framed similar to panels, divider shelves are constructed standard in 6-gauge welded wire mesh. Also available in 16-gauge sheet steel infill for additional separation of contents in stacked units.

HARDWARE: SpaceGuard lockers use heavy duty 5/16" carriage bolts & nuts for panel-to-panel connections. Standard 3/8" wedge anchors supplied for most wall & floor connections on static units.

DOORS: Framed doors with 2 1/2" hinges welded to outer panel frame are offered in single, double or triple tier configurations. Single tier units are also available with slide or bi-parting hinge doors. Doors available in maximum width of 4' to ensure proper operation, although additional wire panels can be attached to extend width of units. Padlock hasps offer adjustability for proper locking.

PORTABLE UNITS: Constructed of same materials as panels, but include heavy-duty 6-gauge welded wire mesh as standard option. Sturdy 2" x 4" steel tube framed base provides stability. Includes 6" x 2" Poly II Urethane swivel wheel casters with wheel brakes. Padlock or 3-point locking rod available. Units can include full or partial depth shelves & ship knocked down or assembled

FINISHES: Two-stage phosphate washed. Standard quick cure, factory-applied powder coat finish in gray. UV & weather resistant. Optional black, yellow, red, blue, green, and white or color match available for nominal upcharge. Now offered in optional hot dipped galvanized & Plascoat finish for humid or corrosive environments.



AUTHORIZED DISTRIBUTOR:

HOW TO ORDER

Submit quantity and type of doors (single or double tier) required including how many of each are starters (2 sides) or adders (1 side). Note unit sizes, height, and whether tops required.

Fax or email plan to our sales team at sales@spaceguardproducts.com

711 South Commerce Drive, Seymour, Indiana 47274
p 800.841.0680 | f 800.428.5758
www.spaceguardproducts.com

